


**DS-MPE-  
SER4OPT 4**  
-Port Opto-  
Isolated Serial  
PCIe MiniCard  
Module



**DIAMOND**  
S Y S T E M S



## FEATURES

4 opto-isolated RS-232/485 serial ports

Maximum baud rate:

1Mbps RS-232 mode

10Mbps RS-485 mode

Available in 3 configurations:

- 4 RS-232 ports
- 4 RS-485 ports
- 2 RS-232 + 2 RS-485 ports

256-byte TX/RX FIFO

SP336 multi-mode transceivers support all modes

+/-500V input/output isolation

Latching connectors for increased ruggedness

+3.3VDC input power

Support for Windows 7, XP, Vista, 2000, and Linux 2.6

Operating temperature -40°C to +85°C

PCIe MiniCard full size form factor (50.95 x 30mm)

## ◆ Description

The DS-MPE-SER4OPT is a rugged, low cost 4-port opto-isolated PCIe MiniCard serial module that is ideal for serial I/O expansion in embedded and OEM applications where opto-isolation is needed for safety or for ground loop prevention.


The DS-MPE-SER4OPT offers 4 RS-232/RS-485 opto-isolated serial ports in a PCIe MiniCard form factor. Each port offers 16C550 compatibility and ultra-deep 256-byte

TX/RX FIFOs. Maximum data rates are 1Mbps in RS-232 mode and 10Mbps in RS-485 mode. The board is available preconfigured for 4 RS-232 ports, 4 RS-485 ports, or a combination of 2 RS-232 and 2 RS-485 ports. I/O signals are provided on two miniature latching connectors, with 2 ports per connector.

Each pair of serial ports on the DS-MPE-SER4OPT offers up to 500V isolation from the system ground. Optoisolation increases reliability in applications with long cable runs, where a difference in ground potential can cause significant ground loop currents, damaging non-isolated boards and equipment. Isolation on this miniature board is achieved through a combination of highly integrated isolated power + data components, careful component placement and layout, and a safety-enhancing insulation film on the bottom side, which prevents accidental contact with components on the carrier board.

DS-MPE-OPT4x is designed for rugged environments with latching connectors and extended temperature capability (-40°C to +85°C). In addition, the board may be custom-configured with 0-ohm resistors in place of jumper blocks for increased ruggedness in high-vibration environments.

The DS-MPE-SER4OPT product comes with the 4-port PCIe MiniCard opto-isolated serial module, the CK-SER4M cable kit, and a hardware kit with jumpers and screws.



## ◆ Specifications

<b>Number of serial ports</b>	4
<b>Protocols</b>	RS-232/485 on each port, configured in pairs
<b>Maximum baud rate</b>	RS-232: 1Mbps RS-485: 10Mbps
<b>Termination</b>	RS-485 jumper selectable
<b>UARTs</b>	Quad XR17V354 with PCIe interface
<b>FIFO</b>	256-byte TX/RX
<b>Transceiver</b>	SP336 multi-mode
<b>Isolation</b>	+/-500V input/output
<b>Input power</b>	+3.3VDC +/-5%

<b>Power consumption</b>	0.462W @ 3.3V
<b>Software drivers</b>	Windows 7, XP, Vista, 2000 Linux 2.6.16, 2.6.27, 2.6.31, 2.6.32
<b>Form Factor</b>	PCIe MiniCard full size
<b>Dimensions</b>	50.95 x 30mm (2 x 1.18")
<b>Operating temperature</b>	-40°C to +85°C
<b>Operating humidity</b>	5% to 95% noncondensing
<b>MTBF</b>	tbd
<b>Weight</b>	8.5g (0.3oz)
<b>RoHS</b>	Compliant

## ◆ Models and Accessories

### DS-MPE-SER4OPT

#### available models:

<b>DS-MPE-OPT4232</b>	4-port RS-232 PCIe MiniCard Opto-Isolated Serial Module	Available
<b>DS-MPE-OPT4485</b>	4-port RS-485 PCIe MiniCard Opto-Isolated Serial Module	Available
<b>DS-MPE-OPT4M22</b>	2-port RS-232, 2-port RS-485 PCIe MiniCard Opto-Isolated Serial Module	Available

Please [login](#) or [signup](#) for an online quote request.

[www.diamondsystems.com](http://www.diamondsystems.com) | [Sunnyvale, California USA](#) | [+1-650-810-2500](tel:+1-650-810-2500) | [sales@diamondsystems.com](mailto:sales@diamondsystems.com)